



Get Centered

To get sound that blows your mind — with power and impact to match the moving image — you need midrange voicing that's precisely articulated.

Proficient Audio has designed a flagship center channel speaker with Kevlar drivers that delivers lifelike sound. And, when you're sitting off-axis — out of the "sweet spot" listening area — the CC550 provides ultra-wide horizontal dispersion for superior tracking with your video screen.

The CC550 is truly a high-end system and features two 5¼" Kevlar woofers that deliver tight, low-end bass. Our twin 2" bass ports help to deliver deeper bass while reducing vent noise and distortion. And with a 3" Kevlar midrange driver, dialog is clear and precise. To top it off, the 1" aluminum dome tweeter gives you smooth, flat response on the high-end of the frequency range. All of this — optimized within a low-resonance cabinet.

If you are looking for really tight, realistic bass, the CC540 is the ticket. It features dual graphite woofers, a graphite mid and aluminum tweeter. If you are looking for a low profile center channel speaker, the CC400 is the one, with dual 4" polypropylene woofers and a 1" aluminum tweeter.

That's quality you can trust. Just what you would expect from Proficient.

CC550
Dual 5¼" Kevlar®



CC540
Dual 5¼" Graphite



CC400
Dual 4" Poly



Proficient Center Channel Specs



CC550

Description	5¼" Kevlar Bookshelf Center Channel
Woofers	Two 5¼" Kevlar Cones
Midrange	3" Kevlar Cone
Tweeter	1" Aluminum Dome
Power Handling	125 Watts
Frequency Response	40Hz-20kHz
Impedance	8Ω
Sensitivity	88dB 1W/1m
Dimensions (H x W x D)	6¾" x 20½" x 8¾"
Warranty	10-Year Limited



CC540

Description	5¼" Graphite Bookshelf Center Channel
Woofers	Two 5¼" Graphite Cones
Midrange	3" Graphite Cone
Tweeter	1" Aluminum Dome
Power Handling	100 Watts
Frequency Response	70Hz-20kHz
Impedance	8Ω
Sensitivity	89dB 1W/1m
Dimensions (H x W x D)	6¾" x 20½" x 8¾"
Warranty	10-Year Limited



CC400

Description	4" Polypropylene Bookshelf Center Channel
Woofers	Two 4" Polypropylene Cones
Tweeter	1" Aluminum Dome
Power Handling	85 Watts
Frequency Response	80Hz-20kHz
Impedance	8Ω
Sensitivity	89dB 1W/1m
Dimensions (H x W x D)	5½" x 20" x 7¼"
Warranty	10-Year Limited